




INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A61G 7/10, 7/053, A44B 11/25		A1	(11) International Publication Number: WO 97/01319
			(43) International Publication Date: 16 January 1997 (16.01.97)
(21) International Application Number: PCT/GB96/00807 (22) International Filing Date: 3 April 1996 (03.04.96) (30) Priority Data: 9512905.2 24 June 1995 (24.06.95) GB (71) Applicant (for all designated States except US): ARJO LIMITED [GB/GB]; St. Catherine Street, Gloucester GL1 2SL (GB). (72) Inventors; and (75) Inventors/Applicants (for US only): SOMERTON, Bruce, Edward [GB/GB]; 4 Mandalay Drive, Norton, Gloucestershire GL2 9LD (GB). COLLINS, Nicholas, Gordon [GB/GB]; 22 Woodcock Lane, Stonehouse, Gloucestershire GL10 2EE (GB). (74) Agent: A R DAVIES & CO.; 27 Imperial Square, Cheltenham GL50 1RQ (GB).		(81) Designated States: AL, AM, AT, AU, AZ, BB, BG, BR, BY, CA, CH, CN, CZ, DE, DK, EE, ES, FI, GB, GE, HU, IS, JP, KE, KG, KP, KR, KZ, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, TJ, TM, TR, TT, UA, UG, US, UZ, VN, ARIPO patent (KE, LS, MW, SD, SZ, UG), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG). Published With international search report.	

(54) Title: AN INVALID HOIST SLING ATTACHMENT DEVICE

(57) Abstract

An invalid hoist sling attachment device comprises a holder (10) attached to or adapted to be attached to a sling hanger of an invalid hoist (or a sling) and a clip (11) attached to or adapted to be attached to the sling (or the sling hanger). The holder comprises a plate-like part (13) and a headed stud (14) projecting from one face of the plate-like part. The clip has a slot (17) comprising a first portion (17a) through which the head of the stud will pass and a second portion (17b) through which the head of the stud will not pass. The holder also has a resilient locking element (18) having at least a portion (19) which protrudes from said one face of the plate-like part to prevent movement of the clip relative to the holder, when the clip is engaged with the headed stud of the holder, into a position in which the head of the stud and the first portion of the slot are aligned without first depressing the resilient locking element.



FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AM	Armenia	GB	United Kingdom	MW	Malawi
AT	Austria	GE	Georgia	MX	Mexico
AU	Australia	GN	Guinea	NE	Niger
BB	Barbados	GR	Greece	NL	Netherlands
BE	Belgium	HU	Hungary	NO	Norway
BF	Burkina Faso	IE	Ireland	NZ	New Zealand
BG	Bulgaria	IT	Italy	PL	Poland
BJ	Benin	JP	Japan	PT	Portugal
BR	Brazil	KE	Kenya	RO	Romania
BY	Belarus	KG	Kyrgyzstan	RU	Russian Federation
CA	Canada	KP	Democratic People's Republic of Korea	SD	Sudan
CF	Central African Republic	KR	Republic of Korea	SE	Sweden
CG	Congo	KZ	Kazakhstan	SG	Singapore
CH	Switzerland	LI	Liechtenstein	SI	Slovenia
CI	Côte d'Ivoire	LK	Sri Lanka	SK	Slovakia
CM	Cameroon	LR	Liberia	SN	Senegal
CN	China	LT	Lithuania	SZ	Swaziland
CS	Czechoslovakia	LU	Luxembourg	TD	Chad
CZ	Czech Republic	LV	Latvia	TG	Togo
DE	Germany	MC	Monaco	TJ	Tajikistan
DK	Denmark	MD	Republic of Moldova	TT	Trinidad and Tobago
EE	Estonia	MG	Madagascar	UA	Ukraine
ES	Spain	ML	Mali	UG	Uganda
FI	Finland	MN	Mongolia	US	United States of America
FR	France	MR	Mauritania	UZ	Uzbekistan
GA	Gabon			VN	Viet Nam

-1-

AN INVALID HOIST SLING ATTACHMENT DEVICE

This invention relates to an invalid hoist sling attachment device for attaching a sling to a sling hanger of an invalid hoist.

5

It is known to provide an attachment device comprising a headed stud, which is secured to the lifting arm of a hoist, and a plate-like clip, which is connected to a sling. The clip is provided with a slot comprising a first portion through which the head of the stud will pass, a second portion through which the head of the stud
10 will not pass and a passage joining the first portion to the second portion. In order to place the clip on the stud, the first portion of the slot is aligned with the head of that stud. The clip is then placed over the stud and moved relative to the stud until the shaft of the stud is disposed in the second portion of the slot. The second portion of the slot receives the shaft of the stud with a clearance so that the clip can pivot
15 about the shaft. The passage receives the shaft of the stud as a friction fit to discourage unintentional movement of the clip from an operative position in which the shaft of the stud is disposed in the second slot portion to a disengageable position in which the shaft of the stud is disposed in the first slot portion.

20

However, it has been found that these known clips do occasionally become unintentionally disengaged from the studs and the present invention seeks to provide an improved attachment device which will make unintentional disengagement less likely.



-2-

According to the present invention there is provided an invalid hoist sling attachment device comprising a holder attached to or adapted to be attached to one of a sling hanger of an invalid hoist and a sling and a clip attached to or adapted to be attached to the other of the sling hanger and the sling, the holder comprising a plate-like part and a headed stud projecting from one face of the plate-like part and the clip having a slot comprising a first portion through which the head of the stud will pass and a second portion through which the head of the stud will not pass, the holder also having a resilient locking element having at least a portion which protrudes from said one face of the plate-like part to prevent movement of the clip relative to the holder, when the clip is engaged with the headed stud of the holder, into a position in which the head of the stud and the first portion of the slot are aligned without first depressing the resilient locking element.

Preferably, the resilient locking element, typically a resilient finger, is defined by a slot, typically of generally U-shape, in the plate-like part of the holder.

Preferably, the holder and clip are made of plastics material.

Preferably, the protruding portion of the resilient locking element is at a free end of the locking element. In this case, advantageously, the protruding portion of the resilient locking element has a ramped surface on its side furthest from the free end of the locking element to assist in engagement of the clip with the holder.

Preferably, the end of the clip closest to the second portion of the slot in the



-3-

clip is part circular to allow the clip to pivot relative to the holder about the headed stud without interference from the resilient locking element. In this case, the clip may have an overhanging lip on its face remote from the holder to make it difficult for a person to depress the locking element except when the clip and the holder are in one
5 or more predetermined angular positions relative to one another.

The invention will now be more particularly described, by way of example, with reference to the accompanying drawings, in which:-

Figure 1 is a perspective view of one embodiment of an attachment device
10 according to the present invention,

Figure 2 is a sectional view taken along the line II - II of Figure 1, and

Figure 3 is a perspective view showing the two parts of the attachment
15 device separated.

Referring to the drawings, the attachment device shown therein comprises a holder 10 which is adapted to be attached to a sling hanger (not shown) of an invalid hoist, e.g. a hoist according to GB 2184706 B, and a clip 11 connected by a flexible
20 strap 12 to a sling (not shown).

The holder 10 comprises a plate-like part 13 and a headed stud 14 projecting from one face of the plate-like part 13. The stud has a stem 15 of circular cross section and a round head 16.



-4-

The clip 11 is plate-like and has a key-hole slot 17 comprising a first part circular portion 17a and a second elongate portion 17b. The diameter of the slot portion 17a is slightly larger than the diameter of the head 16 of the stud 14. The width of the slot portion 17b is less than the diameter of the head 16 of the stud 14 and slightly larger than the diameter of the stem 15 so that when the stem 15 is disposed in the slot portion 17b, the clip 11 can pivot freely about the stud 14 but cannot be disengaged therefrom.

The holder 10 and the clip 11 are made of plastics material, typically glass fibre reinforced nylon.

The holder 10 also has a resilient locking element in the form of a resilient finger 18 formed generally in the plane of the plate-like part 13 and defined by a generally U-shaped slot formed in the plate-like part 13. The finger 18 has at its free end a portion 19 which protrudes from said one face of the plate-like part 13 to prevent movement of the clip 11 relative to the holder 10, when the clip is engaged with the headed stud 14 of the holder, into a position where the head 16 of the stud 14 and the first portion 17a of the slot 17 are aligned without first depressing the finger 18.

20

The finger 18 also has a ramped surface 20 on that side of the protruding portion 19 furthest from the free end of the finger 18 to assist in engagement of the clip 11 with the holder 10.



-5-

The end of the clip 11 closest to the second portion 17b of the slot 17 is part circular (as shown at 21) to allow the clip 11 to pivot relative to the holder 10 about the headed stud 14 without interference from the resilient finger 18.

5 The clip 11 may also have an overhanging lip (not shown) on its face remote from the holder 10 to shield the finger 18 and make it difficult for a person to depress the finger 18 except when the clip 11 and the holder 10 are in one or more predetermined angular positions relative to one another.

10 The holder also has a circular hole 23 which is dimensioned so that it will fit over a conventional headed stud of a sling hanger as a very tight force fit. The holder can therefore be retro-fitted to an existing hoist but it is vital that the dimensions of the hole 23 should be such that it is extremely difficult to remove the holder 10 from the sling hanger once it has been fitted thereto. Alternatively, and as
15 shown, a cross pin can be inserted in holes in the holder 10 to extend across the hole 23 after the holder has been fitted to a sling hanger to ensure that the holder is firmly secured to the sling hanger.

 In order to place the clip 11 on the stud 14, the part circular slot portion
20 17a is aligned with the head 16 of the stud 14. The clip is then pressed firmly towards the plate-like part 13 of the holder 10 to depress the resilient finger 18 and a force is applied to the clip 11 to cause the clip to slide relative to the stud 14 until the stem 15 of the stud is disposed in the slot portion 17b. The resilient finger 18 will then return to its original position and this will prevent removal of the clip 11 from



-6-

the stud 14 without first depressing the finger 18. The clip 11 cannot, therefore, become unintentionally disengaged from the stud 14 and this will give both attendant and user a sense of greater security.

- 5 The overhanging lip, if provided, may ensure that the clip 11 can only be removed from the holder when the longitudinal extent of the slot 17 is generally aligned with the longitudinal extent of the finger 18.

- 10 The embodiment described above is given by way of example only and various modifications will be apparent to persons skilled in the art without departing from the scope of the invention. For example, the holder could be attached to the sling hanger of the hoist in a more permanent manner. Also, the clip and holder could be interchanged with the clip attached to the sling hanger and the holder attached to the sling.



-7-

CLAIMS

1. An invalid hoist sling attachment device comprising a holder attached to or adapted to be attached to one of a sling hanger of an invalid hoist and a sling and a clip attached to or adapted to be attached to the other of the sling hanger and the sling,, the holder comprising a plate-like part and a headed stud projecting from one face of the plate-like part and the clip having a slot comprising a first portion through which the head of the stud will pass and a second portion through which the head of the stud will not pass, the holder also having a resilient locking element having at least a portion which protrudes from said one face of the plate-like part to prevent movement of the clip relative to the holder, when the clip is engaged with the headed stud of the holder, into a position in which the head of the stud and the first portion of the slot are aligned without first depressing the resilient locking element.
2. An invalid hoist sling attachment device as claimed in claim 1, wherein the resilient locking element is defined by a slot in the plate-like part of the holder.
3. An invalid hoist sling attachment device as claimed in claim 2, wherein the resilient locking element is a resilient finger and the slot is of generally U-shape.
4. An invalid hoist sling attachment device as claimed in any one of the preceding claims, wherein the holder and clip are made of plastics material.
5. An invalid hoist sling attachment device as claimed in any one of the





-8-

preceding claims, wherein the protruding portion of the resilient locking element is at a free end of the locking element.

6. An invalid hoist sling attachment device as claimed in claim 5, wherein the
5 protruding portion of the resilient locking element has a ramped surface on its side furthest from the free end of the locking element to assist in engagement of the clip with the holder.

7. An invalid hoist sling attachment device as claimed in any one of the
10 preceding claims, wherein the end of the clip closest to the second portion of the slot in the clip is part circular to allow the clip to pivot relative to the holder about the headed stud without interference from the resilient locking element.

8. An invalid hoist sling attachment device as claimed in claim 7, wherein the
15 clip has an overhanging lip on its face remote from the holder to make it difficult for a person to depress the locking element except when the clip and the holder are in one or more predetermined angular positions relative to one another.



INTERNATIONAL SEARCH REPORT

Inter. al Application No
PCT/GB 96/00807

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A61G7/10 A61G7/053 A44B11/25

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 6 A61G A44B A44C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB,A,2 184 706 (JAMES INDUSTRIES LTD.) 1 July 1987 cited in the application see abstract; claims 1-4; figures 2-4 ---	1-8
A	DE,A,19 55 103 (THE FIRESTONE TIRE & RUBBER COMPANY) 8 October 1970 see figures 1,5-8 ---	1-8
A	AU,A,6 842 274 (ETTRIGE) 30 October 1975 see claims 1-4; figures 1-4 ---	1-8
A	DE,A,30 31 465 (AMBICO, INC.) 26 March 1981 ---	
A	CH,A,619 848 (MEISER & CIE, AG) 31 October 1980 -----	

☐ Further documents are listed in the continuation of box C.

☒ Patent family members are listed in annex.

* Special categories of cited documents :

- * "A" document defining the general state of the art which is not considered to be of particular relevance
- * "E" earlier document but published on or after the international filing date
- * "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- * "O" document referring to an oral disclosure, use, exhibition or other means
- * "P" document published prior to the international filing date but later than the priority date claimed

- * "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention
- * "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- * "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- * "&" document member of the same patent family

Date of the actual completion of the international search

2 July 1996

Date of mailing of the international search report

15. 07. 96

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax (+31-70) 340-3016

Authorized officer

Michels, N

INTERNATIONAL SEARCH REPORT

International Application No
PCT/GB 96/00807

Patent document cited in search report	Publication date	Patent family member(s)	Publication date		
GB-A-2184706	01-07-87	GB-A- 2195978	20-04-88		
		AU-B- 587298	10-08-89		
		AU-B- 6556486	25-06-87		
		BE-A- 905932	16-04-87		
		CA-A- 1288379	03-09-91		
		CH-A- 670384	15-06-89		
		DE-A- 3643612	25-06-87		
		DE-U- 8634100	05-12-91		
		FR-A, B 2591886	26-06-87		
		JP-C- 1678098	13-07-92		
		JP-B- 3041181	21-06-91		
		JP-A- 62155851	10-07-87		
		NL-A, C 8603225	16-07-87		
		SE-B- 466133	07-01-92		
		SE-A- 8605110	22-06-87		
		US-A- 4712257	15-12-87		
		AU-B- 594182	01-03-90		
		AU-B- 7667087	18-02-88		
		BE-A- 1000137	19-04-88		
		CA-A- 1268442	01-05-90		
		CH-A- 672726	29-12-89		
		DE-A- 3725695	25-02-88		
		FR-A, B 2602675	19-02-88		
		JP-C- 1678103	13-07-92		
		JP-B- 3041183	21-06-91		
		JP-A- 63049160	01-03-88		
		NL-A, C 8701918	01-03-88		
		SE-B- 464962	08-07-91		
		SE-A- 8703082	16-02-88		
		US-A- 4742588	10-05-88		

		DE-A-1955103	08-10-70	CA-A- 918386	09-01-73
				FR-A- 2034924	18-12-70
GB-A- 1236527	23-06-71				

AU-A-6842274	30-10-75	NONE			

DE-A-3031465	26-03-81	US-A- 4271999	09-06-81		
		GB-A, B 2063345	03-06-81		
		JP-A- 56033699	04-04-81		

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☒ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.